


REVISIONS			
REV	DESCRIPTION	DATE	NAME
A	Initial Release.	05-17-07	AMH
B	Updated temp spec and labeling	08-17-09	AMH


## FRONT VIEW



Pin#	Assignment
Pin1	Bottom
Pin2	Top
Pin3	Left
Pin4	Right

### NOTES:

- 1.Operation Temperature:-20°C--+60°C  
Storage Temperature:-20°C--+70°C
- 2.Life Time :>1,000,000 times.
- 3.Linearity: ≤1.5%.
- 4.ITO Film:Anti-glare Harding Coating And Anti-Newton Ring Coating  
Sheet Resistance: 400±100 Ω/square;  
ITO Glass: Sheet Resistance: 400±100 Ω/square
- 5.Tail Type :Gold plated FPC
- 6.All Tolerance Without Marked:±0.3
- 7.All Materials and Components must be RoHS compliant
- 8.No Material is allowed to be larger than the glass size



THIS DOCUMENT IS THE PROPERTY OF DAWAR TECHNOLOGIES, INC. AND SHALL NOT BE COPIED, REPRODUCED, DISCLOSED, AND/OR USED AS THE BASIS FOR MANUFACTURING OR SALE WITHOUT PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF DAWAR TECHNOLOGIES, INC.

CUSTOMER NAME	UNIT	DAWAR P/N	REV
Standard product offering	mm	RES6.4-00001	B
CUSTOMER P/N	REV	DRAWN BY	DATE
		Jason Liao	08-17-09
DESCRIPTION	SHEET	MANUFACTURING NO.	REV
6.4" 4-Wire Resistive Touch Screen	1 OF 1		