

DW03761-A



ADVANTAGES

- ▶ Easy to Deploy
- ▶ PCT Multi-touch
- ▶ High Definition
- ▶ Flexible Installation
- ▶ Multi Platform Support
- ▶ Durable and Professional Design



TECHNICAL SPECIFICATIONS

Touch All-in-one With PCT Focus on Industry Touch and Display Solutions

> LCD Panel

Backlight	LED
Brightness	500 cd/m ²
Contrast Ratio	1000:1
Viewing Angle	H:170° / V:160°
Response Time	5 ms (GTG)
Supported Colors	16.7M Colors
Display Resolution	1366 x 768 (16:9)
Display Frame Rate	60Hz
Input Resolution	1366 x 768 @ 60Hz(Analog) 1366 x 768 @ 60Hz(Digital)

> Touch

Touch points	10/no
Touch technology	Projected Capacitive (PCT)

> Mechanical

Dimensions	456.6 x 277.2 x 47 mm
Package Dimension	564.5 x 155 x 402.5 mm
Weight(approximately)	5.5 kg / 7.5 kg
Wall Mount Type	VESA,MIS-D,100,C
Connector	1x VGA /1x HDMI
Operation	0 °C ~ 50 °C, 90% RH
Storage	-20 °C ~ 60 °C, 90% RH

> Electrical

Power Supply	DC in: DC 12V 5A Max
Normal Operation	≤ 19W (typ.)
Power Off	≤ 2 W (typ.)
Internal Speaker	no

> Windows(Options)

CPU	Celeron J3455
GPU	Intel® HD Graphics
Memory	4GB DDR3
Disk	120G SSD
LAN	LAN 10/100/1000 Mbps
WIFI	802.11 b/g/n
Connector	4xUSB /1xLAN /1xHDMI

