

DW03763-A



ADVANTAGES

- ▶ Easy to Deploy
- ▶ High Definition
- ▶ Multi Platform Support
- ▶ PCT Multi-touch
- ▶ Flexible Installation
- ▶ Durable and Professional Design



TECHNICAL SPECIFICATIONS

23.8" Touch All-in-one with PCT Focus on Industry Touch and Display Solutions

> LCD Panel

Backlight	LED
Brightness	550 cd/m ²
Contrast Ratio	1000:1
Viewing Angle	H:178° / V:178°
Response Time	25 ms (GTG)
Supported Colors	16.7M Colors
Display Resolution	1920x 1080 (16:9)
Display Frame Rate	60Hz
Input Resolution	1920 x 1080 @ 60Hz(Analog) 1920 x 1080 @ 60Hz(Digital)

> Touch

Touch points	10/no
Touch technology	Projected Capacitive (PCT)

> Mechanical

Dimensions	577.1 x 349.4 x 47 mm
Package Dimension	685x 155 x 475 mm
Weight(approximately)	7.5 kg / 9.5 kg
Wall Mount Type	VESA,MIS-D,100,C
Connector	1x VGA /1x HDMI
Operation	0 °C ~ 50 °C, 90% RH
Storage	-20 °C ~ 60 °C, 90% RH

> Electrical

Power Supply	DC in: DC 12V 5A Max
Normal Operation	≤ 25W (typ.)
Power Off	≤ 2 W (typ.)
Internal Speaker	no

> Windows

CPU	Celeron J3455
GPU	Intel® HD Graphics
Memory	4GB DDR3
Disk	120G SSD
LAN	LAN 10/100/1000 Mbps
WIFI	802.11 b/g/n
Connector	4xUSB /1xLAN /1xHDMI

